

Vetiver System for Stream Bank Stabilisation

**(With special references to the river and canal bank stabilisation
in Australia and Vietnam)**



Paul Truong

**Director, The Vetiver Network International,
Veticon Consulting, Brisbane, Australia. <**

<truong@uqconnect.net>


Stability of Stream and Water Retaining Structure Banks

1. As in the case of dry land slopes the stability of stream bank is based on the interplay between the driving forces which promote down slope movement, while resisting forces deter movement.
2. However, erosion of water retaining structures are more complicated. it increases driving forces by:
 - Eroding the base of slopes by wave action, which removes the support.
 - Loading, that is, filling previously empty pore spaces and fractures, which adds to the total mass subjected to gravitational force.
 - Reducing the shear strength of the slope material
 - Interacting with surface rock and soil, slowly weakening slope material, and reducing its shear strength. This interaction reduces resisting forces.
3. Failure occurs when erosion of the bank toe and the channel bed have increased the height and angle of the bank to the point that gravitational forces exceed the shear strength of the bank material.

Special Characteristics of Vetiver Suitable for Stream Bank Erosion Control

- **As a wetland plant, Vetiver withstands prolonged submergence. In Cambodia, Vetiver survived longer than five months under the muddy Mekong River water.**
- **Given its extraordinary root depth and strength, mature Vetiver is extremely resistant to washouts from high velocity flow.**
- **Under shallow or low velocity flow, the erect and stiff stems of Vetiver act as a barrier that reduces flow velocity and traps eroded sediment. It can maintain its erect stance in a flow as deep as 0.6-0.8m.**
- **Vetiver leaves will bend under deep and high velocity flow, providing extra protection to surface soil while reducing flow velocity.**
- **When planted on dams or dikes, Vetiver hedgerows help reduce the flow velocity, decrease wave run-up.**
- **These hedgerows also help reduce retrogressive erosion that often occurs when the water flow or wave retreats after it rises.**

Indoor flume test



Water level


Water trickles down

PC: Seth Dabney

In flume test a mature hedge can bank up water to 600mm depth



Water flows over bent leaves and stems



discharge depth

equation

$$q = a \delta y^b y_1^c$$

gradually varied

backwater profile equation

$$\frac{dy}{dx} = \frac{S_0 - S_f}{1 - N_F^2}$$




Figure 1: Hydraulic model of flooding through vetiver.

Where:

q = discharge per unit width
 y = depth of flow

y_1 = depth upstream
 S_0 = land slope

S_f = energy slope
 N_f = the Froude number of flow.

Appropriate Designs and Techniques

As in dry land erosion control, appropriate designs and techniques should be adhered to for successful stream banks erosion control.

For flood mitigation and coastal, riverbank and dike/embankment protection, the following layout specifications are recommended:

- Maximum bank slope should not exceed 1.5(H):1(V).
- Recommended bank slope is 2.5:1.
- Vetiver rows should be planted in two directions, one parallel to flow direction (horizontal), for bank stabilisation and the other right angle to the flow to reduce flow velocity
- The first horizontal row should be planted at the crest of the bank and the last row should be planted at the low water mark of the bank.

Some examples of failures of traditional river bank protection in Vietnam



Soft structure:

Using the water hyacinth barrier.
But Erosion continues behind it

Trees are of not much help either.



Native grass is equally ineffective.

Soft structure



Phragmites spp



From the front it looks like this bank is well protected. But erosion continues as waves from unprotected section upstream got behind it.

Soft structure

**Some examples of river bank
and coastal erosion control
with bamboo, casuarinas
and coconut trees**





Hard structure



Hard structure:

Concrete plate cover on river dike

River and Canal Bank Erosion Control in Australia

- *Bridge Abutment*
- *Drainage channel at Laidley*

Stream bank erosion control in Australia: Bridge abutment




Severe erosion on the abutment of the Coolumboola Creek



Severe erosion on the abutment of the Coolumboola Creek



Vetiver planted after reparation



18 months after planting, no more erosion on the whole site



Five years after planting and after several flash floods




**Yellow leaves due to
winter frost**

**Note the bare area
between rows. No other
plants have survived**




Stabilisation of creek bank of a Dam spillway





One year after planting
The water is brackish

7 7 2001



Flood erosion control in drainage channel

Vetiver hedges were established to spread water out and also to divert water to the drain

Looking sideways towards the channel opening



A big storm hit the area 3 months after planting and the whole site was flooded (Upper section)



Very fast flow flattened and inundated most of the hedges. The velocity was estimated up to 5m/sec in some areas



2 281



Submerged Vetiver
Roots

Drainage channel

Although only 3 month old, the young hedges provide a very effective protection with only minimal erosion at the head of the channel





**Strong flow
exposed part of the
crowns but failed
to dislodge the
plants**



Trapping sediment

General view of channel seven weeks after flooding



River and Canal Bank Erosion Control in Vietnam

- *Failure of rock basket and gabion technique*
- *Success of the Vetiver System*

THE VERY COSTLY ALTERNATIVE

- Rock walls, rock baskets or rip rap are traditional methods used for riverbank stabilisation in Asia, particularly in China and Vietnam.
- These methods are high-tech engineering structures, requiring special skill and high maintenance costs
- These methods are much more expensive, may be several thousand times more in the case of the Mekong delta as rock is not available locally and some imported materials are required
- But most importantly they are not effective as they are not stable themselves on the alluvial plains of Asia. The following photos show their ineffectiveness and high costs.

Viet Nam: The levee bank of the Red river in Hanoi



Gabions and rock baskets are being used to repair recent flood damages which threatened the levee bank of the Red River



A very elaborate and costly engineering structure, these rocks came from far away quarries



Rock basket

Rock rip rap

21/1/33

But this method provided no protection as this bank had been previously covered by similar rock baskets. Remnants of the old rocks which collapsed in the last flood, were still visible in the river.



Consultant Report on costs of riverbank stabilisation in Australia

Summary of the Impacts and Costs Associated of Various Options

Options	Estimated Cost (\$)	Environmental Impacts
Native vegetation	10 000	Low
Vetiver grass	15 000	Low
Dumped riprap	195 000	Low
Rock mattresses	272 500	Medium
Rock groyne	251 250	Low
Concrete pile wall	1 700 000	Medium



Flash flood protection

Levee bank protection in central Vietnam



An irrigation canal in bad shape in central Vietnam



The same site at planting and after several months.



Prawn farm (Brackish water)
dike protection in central
Vietnam

The same site after several
months.



Flood protection

Flood control dike protection
in the Mekong Delta Vietnam

Dike during flood




Water level on the dike
during flood season

Level during dry season



A precious piece of land 5m wide is kept intact due to Vetiver





With Vetiver

Without Vetiver


Eucalyptus is not effective

With Vetiver





Can act alone



With wooden structure



Or with concrete/rock rip-rap structures.



Sea Dikes in north Vietnam



Sea Dikes in south Vietnam

Vetiver protecting sea dike behind the mangrove.



Riverbank Erosion Control in Other Countries

Some examples of VS used in riverbank stabilisation in Cambodia, China, Malaysia, the Philippines, South Africa.



Cambodia
**Erosion on the bank
of the Mekong river**



Cambodia Vetiver planting following earth shaping



Cambodia Eight month after planting





Cambodia
Annual flooding with
depth level between
15-20m



Flood level

Cambodia

Water receded 5 months after flooding:

- the lowest rows (15m) was dead but its roots remain intact and stop erosion

under 15m


8 12 2007

- the mid section (8m) survived and resume growth after water receded

under 8m

8 12 2007

Malaysia: An outstanding success, several floods did not damage this river



***South Africa:* A very well layout provided complete protection against erosion**



Vetiver

J.C. Greenfield.

China: Highly erodible and badly eroded of the often flooded shore line of Lake Evergreen in Guangdong



This section of the bank has been successfully stabilised by vetiver grass in a trial



Philippines: Vetiver was planted to protect the bank of Abra River against flood erosion



Ed Balbarino

One year after planting, the bank was successfully stabilised



Ed Balbarino

THANK YOU



15 6 2007